

MATERIAL SAFETY DATA SHEET



Chem Pack Pty Ltd


ABN 62 060 283 089

120 Fulton Drive Derrimut Vic 3030

incorporating

Citro-Clean Products & Chemlube

(Registered Business Names of Chem Pack Pty Ltd)



Citro-Clean Products
Ph: 61 3 8369 9988

enquiries@chempack.com.au

Chemlube
Ph: 3 8369 9900

Chain Tak Clear Foaming Aerosol Spray

This product is classed as a Dangerous Goods according to criteria of NOHSC.

This product is classified as a Dangerous Goods for transport by road and rail.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Supplier: Chem Pack Pty Ltd
ABN: 62 060 283 089
Street Address: 120 Fulton Drive Derrimut Vic 3030
Telephone: + 61 3 8369 9999
Facsimile: + 61 3 8369 9901
Emergency telephone number: 0412 582 924

Substance: Chemlube Chain Tak Clear Foaming 400g Aerosol Spray
Product name: Chain Tak Clear Foaming Aerosol Spray
Product Use: For lubrication of chains, chain drive systems, conveyors and gears.
Creation Date: 01 April 2009

2. COMPOSITION/INFORMATION ON INGREDIENTS

Recommended Use: For lubrication of chains, chain drive systems, conveyors and gears.

Appearance: Clear liquid, slight odour

Chemical Entity	CAS NO.	Proportion (% weight/weight)
Propane Butane Blend	68475-59-2	25-40%
Aliphatic Hydrocarbon	64742-89-8	25-35%
Polybutene-1	N/Av	10-25%
Tackifier	N/Av	1-10%

3. HAZARDS IDENTIFICATION

A. EMERGENCY OVERVIEW:

Physical Appearance and Odor:
Colourless liquid with slight odour

Warning statements:

Based on available information, classified as hazardous according to health criteria of NOHSC Australia.

B. POTENTIAL HEALTH EFFECTS:

MATERIAL SAFETY DATA SHEET

Eye: May cause irritation.

Skin: May cause irritation and dry out.

Inhalation: Narcotic at high vapour concentrations. Aspiration into the lungs may cause chemical pneumonitis.

Ingestion: May irritate the respiratory tract.

Chronic Effects: Causes serious nerve damage by prolonged exposure resulting in sensory loss. Possible risk of impaired fertility. Can cause headache, dizziness, fatigue, narcosis.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting, give nothing by mouth. SEEK MEDICAL ATTENTION IMMEDIATELY.

Eye contact: Flush immediately, if persistent irritation occurs seek medical assistance.

Skin contact: Wash skin with water using soap if available.

Inhalation: Remove from exposure immediately. If rapid recovery does not occur, obtain medical attention.

Notes to physician: Dermatitis may result from prolonged or repeated exposure. Aspiration into the lungs may cause chemical pneumonitis. Causes central nervous system depression.

5. FIRE-FIGHTING MEASURES

Flash Point: Propellant - 81°C , Active -30°C

Flammability Limits: (% Vol): Lower: 1, Upper: 7.5%

Suitable extinguishing media: Foam. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Hazards from combustion products: Carbon Monoxide may evolve if incomplete combustion occurs.

Precautions for Firefighters and Special Protective Equipment

Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible. In case of fire, use Self Contained Breathing Apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Avoid contact with skin, eyes. Do not breathe vapour. Ventilate contaminated area thoroughly. Cleanup personnel should wear nitrile rubber gloves, gauntlet type, jacket and trousers – nitrile rubber, safety boots – rubber, knee length. Wear full face-piece respirator with organic vapour canister and built-in particulate filter NPF 1000 (gas only). In a confined space wear self-contained breathing apparatus open circuit type NPF 2000.

Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Absorb or contain liquid with sand, earth or spill control material. Shovel up and place in a labeled, sealable container for subsequent safe disposal. Put leaking containers in a labeled drum or overdrum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.

Risk of explosion. Inform the emergency services if liquid enters surface water drains. Vapour may form an explosive mixture with air.

MATERIAL SAFETY DATA SHEET

7. HANDLING AND STORAGE

Precautions for Safe Handling: Avoid prolonged or repeated skin contact. Wash skin thoroughly after handling. Extinguish any naked flames, remove ignition sources, avoid sparks, do not smoke. Take precautionary measures against static discharges.

Precautions for Safe Storage: Keep container tightly closed and in a well ventilated place. Keep away from direct sunlight and other sources heat or ignition. Do not smoke in storage areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits

TWA (8 h) = 50 ppm

TWA (8 h) = 176 mg/m³

Engineering measures: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal protection equipment: Monogoggles, Nitrile rubber gloves, safety shoes or boots – chemical resistant, standard issue work clothes.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Colourless liquid with slight odour.

Specific Gravity (15°C):	0.71 @ 15°C	Melting Point (°C):	N App
Rel. Vapour Density (air=1):	N Av	Boiling Point (°C):	47°C to 120°C
Vapour Pressure (15°C):	Typical, 34.5 kPa	Decomp. Point (°C):	N Av
Sublimation Point:	N App	pH (1% aqueous soln):	N Av
Autoignition Temp (°C):	N Av	Viscosity (20°C):	N Av
% Volatile by volume:	N Av	Evaporation Rate:	N Av
Solubility in water:	N Av		

(Typical values only - consult specification sheet)

N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Stability: Stable under anticipated conditions of storage and handling.

Conditions to Avoid: Heat, flames and sparks.

Incompatible materials: Strong oxidising agents, bases and combustible materials.

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion:	Expected to be of low toxicity, LD50 > 2000 mg/kg
Eye contact:	Not irritating.
Skin contact:	Skin irritant. Expected to be of low toxicity, LD50 > 2000 mg/kg
Inhalation:	Expected to be of low toxicity, LC50 > 5 mg/l

Chronic toxicity: Repeated exposure can cause peripheral neuropathy. Not expected to be mutagenic. Not expected to be a reproductive toxicant. Causes slight foetotoxicity at doses which are maternally toxic. This product contains n-hexane which has been shown to metabolise to compounds which are neuropathic. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. High exposures can cause drowsiness and dizziness. Aspiration into the lungs may cause chemical pneumonitis which can be fatal.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

MATERIAL SAFETY DATA SHEET

Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicity of similar products. Readily biodegradable. Based on product composition. Oxidises rapidly by photo-chemical reactions in air. Integrated environmental half-life expected to be 1 - < 10 days. Has the potential to bioaccumulate. For fish, invertebrates, algae, bacteria and sewage treatment – Expected to be toxic, $1 < LC/EC/IC_{50} \leq 10$ mg/l.

In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

13. DISPOSAL CONSIDERATIONS

For product and waste disposal – recover or recycle if possible. Otherwise incinerate. For container disposal, drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Always comply with local legislation.

14. TRANSPORT INFORMATION

UN Number	1950
Class	2
Packing Group	II

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Based on available information, classified as dangerous goods according to health criteria of NOHSC Australia.

Poisons Schedule (Aust)/Toxic Substance (NZ): 5

16. OTHER INFORMATION

Any advice, recommendation, information, assistance or service provided by Chem Pack Pty Ltd in relation to the goods supplied by it or their use or application is given in good faith and believed to be appropriate and reliable. However, it is provided with a disclaimer for any liability or responsibility on the part of Chem Pack Pty Ltd. The customer accepts all risk and responsibility for use of the goods alone, or in combination with other products. All warranties, guarantees and conditions, other than those expressly stated, and when implied by statute, common law, custom of the trade or otherwise, are to the extent that the law permits, expressly excluded.