

# MATERIAL SAFETY DATA SHEET



## Chem Pack Pty Ltd


ABN 62 060 283 089

120 Fulton Drive Derrimut Vic 3030

incorporating

## Citro-Clean Products & Chemlube

(Registered Business Names of Chem Pack Pty Ltd)



Citro-Clean Products  
Ph: 61 3 8369 9988

[enquiries@chempack.com.au](mailto:enquiries@chempack.com.au)

Chemlube  
Ph: 3 8369 9900

## Lube Wizz WD Aerosol Spray

This product is classed as Hazardous according to criteria of NOHSC.

This product is classified as a Dangerous Goods for transport by road and rail.

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Supplier:** Chem Pack Pty Ltd  
**ABN:** 62 060 283 089  
**Street Address:** 120 Fulton Drive Derrimut Vic 3030  
**Telephone:** + 61 3 8369 9999  
**Facsimile:** + 61 3 8369 9901  
**Emergency telephone number:** 0412 582 924

**Substance:** Chemlube Lube Wizz 400g Aerosol Spray  
**Product name:** Lube Wizz Aerosol Spray  
**Product Use:** WD spray  
**Creation Date:** 01 April 2009

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Recommended Use:** As a multi-purpose lubricant, water displacer, degreaser, penetrator and to prevent corrosion.

**Appearance:** Opaque liquid with petroleum odour

Chemical Entity	CAS NO.	Proportion (% weight/weight)
Propane Butane Blend	68475-59-2	25-40%
Aliphatic Hydrocarbon	64742-89-8	40-55%
Kerosene	N/Av	15-35%
Propar32	N/Av	5-15%
Vegetable oil	8002-13-9	5-15%

### 3. HAZARDS IDENTIFICATION

#### A. EMERGENCY OVERVIEW:

**Physical Appearance and Odor:**

Opaque liquid with petroleum odour

**Warning statements:**

Based on available information, classified as hazardous according to health criteria of NOHSC Australia.

# MATERIAL SAFETY DATA SHEET

## B. POTENTIAL HEALTH EFFECTS:

**Eye:** N/A

**Skin:** Irritating to the skin. Causes serious nerve damage by prolonged exposure resulting in sensory loss.

**Inhalation:** Danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility Aspiration into the lungs may cause chemical pneumonitis which can be fatal. Narcotic at high vapour concentrations.

**Ingestion:** N/A

**Chronic Effects:** N/A

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

## 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting, give nothing by mouth. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

**Eye contact:** Flush eye with water. If persistent irritation occurs obtain medical attention.

**Skin contact:** Wash skin with water using soap if available.

**Inhalation:** Remove from exposure immediately. If rapid recovery does not occur, obtain medical attention.

**Notes to physician:** Dermatitis may result from prolonged or repeated exposure. Aspiration into the lungs may cause chemical pneumonitis. Causes central nervous system depression.

## 5. FIRE-FIGHTING MEASURES

**Flash Point:** Propellant - 81°C , Active < -23°C

**Flammability Limits: (% Vol):** No Data.

**Suitable extinguishing media:** Use carbon dioxide, dry chemical powder or regular dry foam as extinguishing media. Sand or earth may be used for small fires.

**Hazards from combustion products:** Could evolve carbon monoxide if incomplete combustion occurs. Flammable gas. Dangerous hazard when exposed to heat or flame. Severe vapour explosion hazard, when exposed to flame or spark. Gas may form explosive mixtures with air over a wide area.

### Precautions for Firefighters and Special Protective Equipment

Will float and can be reignited on surface water. The vapour is heavier than air, spreads along the ground and distant ignition is possible. May be violently explosive or reactive. In case of fire, wear full body protection and Self Contained Breathing Apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

**Cleanup and Disposal of Spill:** Avoid contact with skin, eyes. Do not breathe vapour. Ventilate contaminated area thoroughly. Cleanup personnel should wear nitrile rubber gloves, gauntlet type, jacket and trousers – nitrile rubber, safety boots – rubber, knee length. Wear full face-piece respirator with organic vapour canister and built-in particulate filter NPF 1000 (gas only). In a confined space wear self-contained breathing apparatus open circuit type NPF 2000. Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Absorb or contain liquid with sand, earth or spill control material. Shovel up and place in a labeled, sealable container for subsequent safe disposal. Put leaking containers in a labeled drum or

# MATERIAL SAFETY DATA SHEET

overdrum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.

Risk of explosion. Inform the emergency services if liquid enters surface water drains. Vapour may form an explosive mixture with air.

## 7. HANDLING AND STORAGE

**Precautions for Safe Handling:** Avoid breathing vapours, use local exhaust extraction. Avoid accidents, clean up immediately. Avoid prolonged or repeated skin contact. Wash skin thoroughly after handling. Extinguish any naked flames, remove ignition sources, avoid sparks, do not smoke. Take precautionary measures against static discharges.

**Precautions for Safe Storage:** Protect from physical damage. Store in a cool, dry place. Ventilation required. Avoid direct sunlight, heat, flames, sparks and other sources of ignition. Store in tightly closed containers. Store under an inert atmosphere. Keep separated from incompatible substances. Keep away from ignition sources at all times. Store aerosols in cool, dry environment below 38°C. Avoid storage with oxidizers, bases and combustible materials.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits

TWA (8 h) = 200 ppm

TWA (8 h) = 770 mg/m<sup>3</sup>

**Engineering measures:** Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

**Personal protection equipment:** Use splash resistant safety goggles with a faceshield, appropriate chemical resistant clothing, chemical resistant gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form / Colour / Odour:** Opaque liquid with petroleum odour

Specific Gravity (15°C):	0.75	Melting Point (°C):	N App
Rel. Vapour Density (air=1):	N Av	Boiling Point (°C):	14°C to 135°C
Vapour Pressure (20°C):	N Av	Decomp. Point (°C):	N Av
Sublimation Point:	N App	pH (1% aqueous soln):	N Av
Autoignition Temp (°C):	N Av	Viscosity (20°C):	N Av
% Volatile by volume:	<50%	Evaporation Rate:	N Av
Solubility in water:	>1%		

(Typical values only - consult specification sheet)

N Av = Not available N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under anticipated conditions of storage and handling.

**Conditions to Avoid:** Heat, flames and sparks.

**Incompatible materials:** Strong oxidising agents, bases and combustible materials.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

### Acute Effects

**Ingestion:** Expected to be of low toxicity, LD50 > 2000 mg/kg.

**Eye contact:** Not irritating.

**Skin contact:** Skin irritant. Expected to be of low toxicity, LD50 > 2000 mg/kg.

**Inhalation:** Expected to be of low toxicity, LD50 > 5 mg/l

# MATERIAL SAFETY DATA SHEET

**Chronic toxicity:** Not expected to be mutagenic. Not expected to be a reproductive toxicant. Repeated exposure can cause peripheral neuropathy. Causes slight foetotoxicity at doses which are maternally toxic. This product contains n-hexane which has been shown to metabolise to compounds which are neuropathic. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. High exposures can cause drowsiness and dizziness. Aspiration into the lungs may cause chemical pneumonitis which can be fatal.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity:

Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

Floats on water. Evaporates within a day from water or soil surfaces.

Readily biodegradable. Based on product composition. Oxidises rapidly by photo-chemical reactions in air. Integrated environmental half-life expected to be 1 - < 10 days. Has the potential to bioaccumulate.

For fish, invertebrates, algae, bacteria and sewage treatment: Expected to be toxic,  $1 < LC/EC/IC 50 < 10 \text{ mg/l}$ .

In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

## 13. DISPOSAL CONSIDERATIONS

For product or waste disposal, recover or recycle if possible. Otherwise incinerate.

For container disposal, drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer.

Always comply with local legislation.

## 14. TRANSPORT INFORMATION

UN Number 1950

Class 2

Packing Group II

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

Based on available information, classified as dangerous goods according to health criteria of NOHSC Australia.

**Poisons Schedule (Aust)/Toxic Substance (NZ): 5**

## 16. OTHER INFORMATION

Any advice, recommendation, information, assistance or service provided by Chem Pack Pty Ltd in relation to the goods supplied by it or their use or application is given in good faith and believed to be appropriate and reliable. However, it is provided with a disclaimer for any liability or responsibility on the part of Chem Pack Pty Ltd. The customer accepts all risk and responsibility for use of the goods alone, or in combination with other products. All warranties, guarantees and conditions, other than those expressly stated, and when implied by statute, common law, custom of the trade or otherwise, are to the extent that the law permits, expressly excluded.