# PRODUCT SPECIFICATION SHEET



Phone: 03 8369 9900 Fax: 03 8369 9901

Email: enquiries@chemlube.com.au

Web: www.chemlube.com.au

# Concentrated Silicone Spray

**Silicone Spray** is the best spray lubricant for general-purpose lubrication or release agent for moulding plastics.

**Silicone Spray** is a formulated lubricant with a temperature range between – 30°C to +300°C. It is a blend of colourless, non-toxic and non-staining silicone concentrates designed to meet a range industrial applications.

**Silicone Spray** meets the MIL-S-18660 Specification and is classified as Food Grade (Incidental Contact) for use in food packaging / manufacturing applications.

#### Features:

- Reduces friction, sticking, adhesion and wear.
- Odourless
- Lubrication suitable for High Temperature

#### **Recommended Uses:**

- Mould Release Agent Injection & Resin Moulding
- Lubricate gym equipment ie. Treadmills and other fitness machines
- Embriodery and Sewing machines, eliminating thread sticking and breakage
- Free stuck zippers and lubricate
- Lubricate curtain tracks, sliding doors and windows, zippers
- Printing Industry
- Lubricate conveyors, chains, hinges, cutting blades, heat sealers, and much more
- Create slip on plastic and steel benches
- Lubricate valves, rubber seals and o'rings
- Minimise effects of corrosion on metal surfaces

# **Additional Information:**

Silicone Spray may prevent the adhesion of paints or adhesives. In these applications, we recommend "Paintable" products which retain the silicone characteristics without the disadvantages where paintability is required.

### **Pack Sizes:**

- 400g Aerosol cartons of 12
- 20 Litres







1 of 1 Product: Concentrated Silicone Spray Issued: May 14